

INSTRUCTION MANUAL

Repair Straight Pipes under pressure
while the system is ON

Magicawrap- Tape (S Set)

Product	Dia. of pipe to apply
MTRS 25-5	upto 25 mm
MTRS 40-5	upto 40 mm
MTRS 50-5	upto 50 mm
MTRS 65-5	upto 65 mm
MTRS 75-5	upto 75 mm
MTRS 100-5	upto 100 mm
MTRS 125-5	upto 125 mm
MTRS 150-5	upto 150 mm
MTRS 200-5	upto 200 mm
MTRS 250-5	upto 250 mm

Pressure: Basically 0.5MPa (5Kg/cm²) or under

Please read this document before you start work so that it will be safe and effective.

Requirements for use:

- Warranty period is shown on the aluminum foil package.
- **DO NOT** Open the package of Magicawrap until you start applying as moisture in the air will activate the resin in Magicawrap.
- Please apply the entire Magicawrap as unused Magicawrap will be hardened.
- No incidents nor consecutive damages are indemnified unless the products are determined defective by our quality control standard.
- All defective products shall be replaced with new ones.
- Wrong or misuse is not indemnified.

Product Configuration

Product	Magicawrap	Magicawrap-Tape	Latex Gloves
MTRS 25-5	MT-205 1pc	Stype 25-5 1pc	1set
MTRS 40-5	MT-205 1pc	Stype 40-5 1pc	1set
MTRS 50-5	MT-205 1pc	Stype 50-5 1pc	1set
MTRS 65-5	MT-309 1pc	Stype 65-5 1pc	1set
MTRS 75-5	MT-309 1pc	Stype 75-5 1pc	1set
MTRS100-5	MT-415 1pc	Stype 100-5 1pc	1set
MTRS125-5	MT-420 1pc	Stype 125-5 1pc	4set
MTRS150-5	MT-430 1pc	Stype 150-5 1pc	4set
MTRS200-5	MT-430 1pc	Stype 200-5 1pc	4set
MTRS250-5	MT-440 1pc	Stype 250-5 1pc	4set



บริษัท สยามราชธานี (ตะวันออก) จำกัด

Siam Rajathanee (East) Co., Ltd.

สนง.ใหญ่ (ระยอง) : 15/1 ถ.ทางหลวงระยองสาย 3191 ต.ท้ายโป่ง อ.เมือง จ.ระยอง 21150
Tel : 038-682540 (Auto) Fax : 038-682539

สาขา (กรุงเทพฯ) : 128/240 ซ.ไทยประกัน 1/4 ถ.เทพารักษ์ ต.บางเสาธง อ.บางเสาธง
จ.สมุทรปราการ 10540 Tel : 02-7064521 Fax : 02-7064522

E-mail : info@siameast.co.th www.siameast.co.th

Recommendable Use.

- You can repair the pipe under pressure while the system is ON.
* Please select the most suitable package depending on the pipe diameter for repair.
- Effective for wide range of pipe material:
Steel, Stainless, Copper, Plastic, Polypropylene, Polyethylene, Lead etc.

WARNING (for your Safety)

- When winding Magicawrap-Tape (pressure sealing rubber tape) around the pipe, using too much force can cause your hand to slip or cause operator to get off balance.
- **DO NOT** touch Magicawrap with your bare hands. Avoid contact to your unprotected skin or eyes. **Be sure to use a pair of protective Latex gloves for handling of Magicawrap.** The resin used in Magicawrap will adhere to skin and clothing and may cause skin irritation.
- In case you have touched Magicawrap, wipe out lightly with alcohol or rinse with soap and water for more than 5 minutes.
- If eyes are exposed to the resin, rinse eyes with water for approx. 15 minutes and then contact a doctor.
- Any tools contaminated with the resin in Magicawrap, must be cleaned with alcohol or acetone prior to the resin curing.

- **DO NOT** Open the package of Magicawrap until you start applying as moisture in the air will activate the resin in Magicawrap
Please apply the entire roll of Magicawrap, as unused Magicawrap will be hardened